

General Specifications

DOUBLE 4 Digit, 4" LED Clock

model: HY-2X4-4

SELENA
LED Digital Clocks

ALL CLOCKS INCLUDE REMOTE CONTROL

FLUSH / SURFACE MOUNT
METAL ENCLOSURE

4" HIGH DIGITS

RED, GREEN, YELLOW, BLUE

→
EXAMPLE of the display setup as
CLOCK + TIMER



←
EXAMPLE of the display setup as
CLOCK + TEMPERATURE

Dimensions:
24.25" x 5.75" x 2.5"
(61.6cm x 14.6cm x 6.4cm)

The Display can be set to alternate between CLOCK, Timer, Date, Temperature, Julian etc...



Multifunction Remote Control Included

FEATURES and OPTIONS:

- * Infra Red hand held REMOTE CONTROL for all functions
- * Direct Replacement for existing MASTER SYSTEM CLOCKS (replaces round, mechanical or electronic)
- * 12 or 24 Hour and Military Display Format (user selectable)
- * Multiple Master-Slave correction modes:
 - Power Line Carrier sync (Simplex)
 - 2 Wire, RS485 Twisted Pair Sync/Communication
 - BCD digital, ASCII Time Code
 - RS232 (PC port) or RS485
 - 2 and 3 Wire, 24V Minute Impulse Sync
- * Multi-Zone synchronized system
- * Temperature Monitoring and Control:
 - Multi-Event Programmable Thermostat
 - Heating - Cooling Auto Change-Over
 - Inside and Outside Thermometer function
 - Min/Max Temperature Memory
 - Temperature Alarm and Relay outputs
- * Stand - Alone or Master - Slave
- * Backup:
 - Selfrecharging backup - NO BATTERY NEEDED
 - 10 Year Lithium battery option
- * Atomic Clock or GPS option
- * PC Sync Master option
- * Day/Date/Month/Year Alternating display selection
- * Fully Adjustable Brightness
 - Manual via remote control
 - Auto-dimming option
- * Julian Day option
- * Auto Leap-Year correction
- * Day Light Savings correction
- * Timers:
 - Multi-Event Programmable Timer
 - Wake-Up Alarm Timer with soft beeper control
 - Stop-Watch function up to 1/100 sec resolution
 - External Start/Stop/Reset switch inputs
 - Up/Down Presettable Timer and Counter with Alarm (up to 99hrs:59min:59sec or 99999 counts)
- * On-Board Alarms:
 - Alarm Buzzer, internal or external Horns
 - Alarm Relays (Form C, 10Amp/240V)
- * NON-GLARE lens
- * NON-MULTIPLEXING - Camera friendly

4 DIGIT TIME DISPLAY modes:

MODE 1: *HH:MM (12 hour format with am/pm dot)
 MODE 2: HH:MM (24 hour format)
 MODE 3: HH:MM (24 hour Military format)
 MODE 4: HH:MM (UP/DOWN Timer modes with Hrs:Min)
 MODE 5: MM:SS (UP/DOWN Timer modes with Min:Sec)
 MODE 6: d 267 (JULIAN DAY)
 MODE 7: 9999 (UP/DOWN Counter modes)

DATE DISPLAY modes:

MODE 8: Oc.07
 MODE 9: 12.Fr
 MODE 10: 12.Oc

TEMPERATURE DISPLAY modes:

MODE 11: In 25 C (or: 77 F)
 MODE 12: Out 16 C (or: 61 F)
 MODE 13: 25 C (or: 77 F)

OTHER OPTIONS:


1. INTERNAL POWER SUPPLY FOR 115V or 220V , 50/60Hz
2. 12V and 24V DC or AC SUPPLY OPTION
3. SYSTEM MASTER SYNC WITH RS-232/485 COMPUTER INTERFACE / TWISTER PAIR
4. SYSTEM MASTER SYNC WITH SERIAL COMMUNICATION OVER POWER LINE
5. SYSTEM MASTER SYNC OVER POWER LINE CARRIER (HIGH AND LOW VOLTAGE)
6. SYSTEM MASTER SYNC 2 AND 3 WIRE, 24 VOLT MINUTE IMPULSE
7. SYSTEM MASTER SYNC ASCII TIME CODE FORMAT 0, 1, 2, 3, 4 ON RS-232/485





DOUBLE 4 Digits, 4" Metal Enclosure

ALL CLOCKS INCLUDE REMOTE CONTROL

standard colors: white, black and stainless steel





STRAIGHT MODEL
option # 732



Short cord with flat plug shown
Optional:
Long cord or Screw terminal
for power connection

SLANTED MODEL
Option # 733



Short cord with flat plug shown
Optional:
Long cord or Screw terminal
for power connection