

General Specifications

6 Digit Time & Date / Text LED Clock

SELENA
LED Digital Clocks

model: HYTX-6(U)L-4

ALL CLOCKS INCLUDE REMOTE CONTROL

FLUSH / SURFACE MOUNT
METAL ENCLOSURE


4" TIME 2.3" DATE / TEXT
with Smaller Seconds, Upper or Lower

RED, GREEN, YELLOW, BLUE



Multifunction Remote Control Included

Dimensions:
24.5" x 10" x 3"
(62.3cm x 25.4cm x 7.6cm)



TEXT and/or Digits can be set to alternate between TEXT, Date, Temperature, Julian etc...

FEATURES and OPTIONS:

- * **Infra Red hand held REMOTE CONTROL for all functions**
- * **Direct Replacement for existing MASTER SYSTEM CLOCKS** (replaces round, mechanical or electronic)
- * 12 or 24 Hour and Military Display Format (user selectable)
- * Multiple Master-Slave correction modes:
 - Power Line Carrier sync (Simplex)
 - 2 Wire, RS485 Twisted Pair Sync/Communication
 - BCD digital, ASCII Time Code
 - RS232 (PC port) or RS485
 - 2 and 3 Wire, 24V Minute Impulse Sync
- * Multi-Zone synchronized system
- * Temperature Monitoring and Control:
 - Multi-Event Programmable Thermostat
 - Heating - Cooling Auto Change-Over
 - Inside and Outside Thermometer function
 - Min/Max Temperature Memory
 - Temperature Alarm and Relay outputs
- * Stand - Alone or Master - Slave
- * Backup:
 - Selfrecharging backup - NO BATTERY NEEDED
 - 10 Year Lithium battery option
- * Atomic Clock or GPS option
- * PC Sync Master option
- * Day/Date/Month/Year Alternating display selection
- * Fully Adjustable Brightness
 - Manual via remote control
 - Auto-dimming option
- * Julian Day option
- * Auto Leap-Year correction
- * Day Light Savings correction
- * Timers:
 - Multi-Event Programmable Timer
 - Wake-Up Alarm Timer with soft beeper control
 - Stop-Watch function up to 1/100 sec resolution
 - External Start/Stop/Reset switch inputs
 - Up/Down Presettable Timer and Counter with Alarm (up to 99hrs:59min:59sec or 999999 counts)
- * On-Board Alarms:
 - Alarm Buzzer, internal or external Horns
 - Alarm Relays (Form C, 10Amp/240V)
- * NON-GLARE lens
- * NON-MULTIPLEXING - Camera friendly

6 DIGIT TIME DISPLAY modes:

- MODE 1: *HH:MM SS (12 hour format with am/pm dot)
- MODE 2: HH:MM SS (24 hour format)
- MODE 3: HH:MM PM (12 hour format with am/pm text)
- MODE 4: HH:MM SS (24 hour Military format)
- MODE 5: HH:MM SS (UP/DOWN Timer modes)
- MODE 6: MM:SS^{hh} (UP/DOWN Timer modes with 1/100 sec)
- MODE 7: d 267⁰⁷ (JULIAN DAY with Year)

NOTE: Display with **UPPER** or **LOWER** seconds available

OTHER OPTIONS:

1. INTERNAL POWER SUPPLY FOR 115V or 220V , 50/60Hz
2. 12V and 24V DC or AC SUPPLY OPTION
3. SYSTEM MASTER SYNC WITH RS-232/485 COMPUTER INTERFACE / TWISTER PAIR
4. SYSTEM MASTER SYNC WITH SERIAL COMMUNICATION OVER POWER LINE
5. SYSTEM MASTER SYNC OVER POWER LINE CARRIER (HIGH AND LOW VOLTAGE)
6. SYSTEM MASTER SYNC 2 AND 3 WIRE, 24 VOLT MINUTE IMPULSE
7. SYSTEM MASTER SYNC ASCII TIME CODE FORMAT 0, 1, 2, 3, 4 ON RS-232/485

DATE/TEXT DISPLAY modes:

- MODE 1: FRI-OCT-12
- MODE 2: OCT-12-FRI
- MODE 3: 12-OCT-FRI
- MODE 4: FRI-12-OCT
- MODE 5: 12-OCT-2007
- MODE 6: OCT-12-2007
- MODE 7: 2007-12-OCT
- MODE 8: HH-MM-SS (timer or counter)
- MODE 9: TIMER MM-SS (timer)
- MODE 10: DDD-HH-MM.SS (timer or counter)
- MODE 11: IN 25.3 C (or: 77.5 F)
- MODE 12: OUT 16.4 C (or: 61.5 F)
- MODE 13: TEMP. 25.3 C (or: 77.5 F)
- MODE 14: DAY 245 (Julian day of the year)
- MODE 15: HH-MM-SS AM/PM (Real Time Clock)
- MODE 16: TIME ZONE / TEXT DISPLAY

Metal Enclosure

standard colors: white, black and stainless steel

