

model series: HYMSF-6S-2.3 and HYMSF-6(U)L-2.3

**Super Bright LEDs: RED, GREEN, YELLOW or BLUE - 2.3 INCH High, 6 Digits
with SAME SIZE or SMALLER SECONDS (Upper or Lower)**

FEATURES and Options:

- * Infra Red hand held REMOTE CONTROL for all functions
- * Direct Replacement for existing MASTER - SLAVE SYSTEM CLOCKS (replaces round, mechanical or electronic)
- * 12 or 24 Hour and Military Display Format (user selectable)
- * Multiple Master-Slave correction modes:
 - Master-Slave Power Line Carrier sync (Simplex)
 - Master-Slave 2 Wire, RS485 Twisted Pair Sync/Communication
 - Master-Slave BCD digital, ASCII Time Code
 - RS232 and RS485 serial communication (PC port)
 - Master-Slave 2 and 3 Wire, 24V Minute Impulse Sync
- * Multi-Zone synchronized Master-Slave system
- * Temperature Monitoring and Control:
 - Multi-Event Programmable Thermostat
 - Heating - Cooling Auto Change-Over
 - Inside and Outside Thermometer function
 - Min/Max Temperature Memory
 - Temperature Alarm and Relay outputs
- * Stand - Alone operation for Home or Office
- * Backup:
 - Self-recharging backup - NO BATTERY NEEDED
 - 10 Year Lithium battery option
- * Atomic Clock option
- * PC Sync Master option
- * Day/Date/Month/Year Alternating display selection
- * Fully Adjustable Brightness
 - Manual via remote control
 - Auto-dimming option
- * Julian Day option
- * Auto Leap-Year correction
- * Day Light Savings correction
- * Timers:
 - Multi-Event Programmable Timer
 - Wake-Up Alarm Timer with soft beeper control
 - Stop-Watch function up to 1/100 sec resolution
 - External Start/Stop/Reset switch inputs
 - Up/Down Presettable Timer and Counter with Alarm (up to 99hrs:59min:59sec or 999999 counts)
- * On-Board Alarms:
 - Alarm Buzzer, internal or external Horns
 - Alarm Relays (Form C, 10Amp/240V)
- * NON-GLARE lens
- * NON-MULTIPLEXING - Camera friendly
- * Variety of enclosures:
 - Black - White - Stainless Steel - Custom Colors

Flush Mount, Metal, Straight Enclosure



Multifunction
Remote Control
Included

SPECIFICATIONS:

Supply Voltage:	115V or 208-240V, 50/60Hz 24 or 12V AC/DC
Power:	6VA average
Operating Temperature:	0C to +50C (32F to 122F) (military range optional)
Humidity:	95% RH max. non cond.
Dimensions Face w/flange:	15.25" x 5.25" x 2.5" (38.7cm x 13.4cm x 6.3cm)
Visibility:	Easy up to 80Ft. (25m)

HIGH RELIABILITY SELENA Clocks are ideal for **DIRECT REPLACEMENT** of obsolete and failing Master-Slave system clocks like round electro-mechanical clocks.

Just take down old clocks and hang up SELENA Clocks. No additional mounting brackets or wiring necessary.

All functions and presets may be accessed via hand held remote control just like TV remote. If Power Fails, even WITHOUT Battery clock will accurately work for over 2 weeks. With Auto-dimming option display will dimm down automatically in the evening or when lights are turned off. Display will become brighter with bright ambient light.

Inside and Outside Temperature Display option shows current weather conditions. Alarm buzzer and thermostat options with internal relay can control heating and A/C cooling. Relaxing, No-Flicker, camera friendly display technology (new). Choose Thermometer, Programmable Timer, Alarm Clock functions with Remote Control.

**Best priced on the market. Most Features.
Easiest to INSTALL and USE in its class.**

