

model series: HYMAR-6S-2.3R(G,Y,B).....732S23WP

FLUSH / SURFACE MOUNT      6 DIGITS, 2.3" LED DISPLAY      **RED, GREEN, YELLOW, BLUE**  
with Same Size Seconds

**FEATURES:**

- \* **Infra Red hand held REMOTE CONTROL for all functions**
- \* **Direct Replacement for existing MASTER SYSTEM CLOCKS**  
(replaces round, mechanical or electronic)
- \* 12 or 24 Hour and Military Display Format (user selectable)
- \* Multiple correction Master-Slave modes:
  - Power Line Carrier sync (Simplex)
  - 2 Wire, RS485 Twisted Pair Sync/Communication
  - BCD digital, ASCII Time Code
  - RS-232 ( PC port )
  - 2 and 3 Wire, 24V Minute Impulse Sync
- \* Multi-Zone synchronized system
- \* Temperature Monitoring and Control:
  - Multi-Event Programmable Thermostat
  - Heating - Cooling Auto Change-Over
  - Inside and Outside Thermometer function
  - Min/Max Temperature Memory
  - Temperature Alarm and Relay outputs
- \* Stand - Alone operation for Home or Office
- \* Backup:
  - Selfrecharging backup - NO BATTERY needed
  - 10 Year Lithium battery option
- \* PC Sync Master-Slave option
- \* Day/Date/Month/Year Alternating display selection
- \* Fully Adjustable Brightness
  - Manual via remote control
  - Auto-dimming option
- \* Julian Day option
- \* Auto Leap-Year correction
- \* Day Light Savings correction
- \* Timers:
  - Multi-Event Programmable Timer
  - Wake-Up Alarm Timer with soft beeper control
  - Stop-Watch function up to 1/100 sec resolution
  - External Start/Stop/Reset switch inputs
  - Up/Down Presettable Timer and Counter with Alarm  
(up to 99hrs:59min:59sec)
- \* On-Board Alarms:
  - Alarm Buzzer, internal or external Horns
  - Alarm Relays ( Form C, 10Amp/240V )
- \* NON-GLARE lens
- \* NON-MULTIPLEXING - Camera friendly

Surface Mount ( or optional Flush Mount )  
Water-Proof Enclosure  
Stainless Steel painted with backed enamel



Multifunction  
Remote Control  
Included



**SPECIFICATIONS:**

Supply Voltage:	115V, 208-240V, 50/60Hz 24 or 12V AC/DC
Power:	6VA average
Operating Temperature:	0C to +50C (32F to 122F)
Humidity:	95% RH max. non cond.
Dimensions (w/o back flange)	15" x 5" x 2.5" (38.1cm x 12.7cm x 6.3cm)
Back Flange:	Add 0.5" (1.27cm) on each side and depth
Visibility:	Easy up to 80Ft. (25m)

**HIGH RELIABILITY** SELENA Clocks are ideal for **DIRECT REPLACEMENT** of obsolete and failing system clocks like round electro-mechanical clocks.

Just take old ones down and hang up SELENA Clocks. No additional mounting brackets or wiring necessary.

All functions and presets may be accessed via hand held remote control just like TV remote. If Power Fails, even **WITHOUT** Battery clock will accurately work for up to 2 weeks. With Auto-dimming option display will dimm down automatically in the evening or when lights are turned off. Display will become brighter with bright ambient light.

Inside and Outside Temperature Display option shows current weather conditions. Alarm buzzer and thermostatic, internal relay can control heating or cooling. Relaxing, No-Flicker, camera friendly display technology (new). Choose Thermometer, Timer, Alarm Clock functions with Remote Control.

**Best priced on the market. Most Features.**  
**Easiest to INSTALL and USE in its class.**