

# Marine Waterproof St. Steel **Selena** with REMOTE CONTROL

model series: HYMAR-6U(L)-2.3R(G,Y,B).....732S23WP

FLUSH / SURFACE MOUNT      6 DIGITS, 2.3" LED DISPLAY      **RED, GREEN, YELLOW, BLUE**  
with Smaller Upper or Lower Seconds

**FEATURES:**

- \* **Infra Red hand held REMOTE CONTROL for all functions**
- \* **Direct Replacement for existing MASTER SYSTEM CLOCKS**  
(replaces round, mechanical or electronic)
- \* 12 or 24 Hour and Military Display Format (user selectable)
- \* Multiple correction Master-Slave modes:  
Power Line Carrier sync (Simplex)  
2 Wire, RS485 Twisted Pair Sync/Communication  
BCD digital, ASCII Time Code  
RS-232 ( PC port )  
2 and 3 Wire, 24V Minute Impulse Sync
- \* Multi-Zone synchronized system
- \* Temperature Monitoring and Control:  
Multi-Event Programmable Thermostat  
Heating - Cooling Auto Change-Over  
Inside and Outside Thermometer function  
Min/Max Temperature Memory  
Temperature Alarm and Relay outputs
- \* Stand - Alone operation for Home or Office
- \* Backup:  
Selfrecharging backup - NO BATTERY needed  
10 Year Lithium battery option
- \* PC Sync Master-Slave option
- \* Day/Date/Month/Year Alternating display selection
- \* Fully Adjustable Brightness  
Manual via remote control  
Auto-dimming option
- \* Julian Day option
- \* Auto Leap-Year correction
- \* Day Light Savings correction
- \* Timers:  
Multi-Event Programmable Timer  
Wake-Up Alarm Timer with soft beeper control  
Stop-Watch function up to 1/100 sec resolution  
External Start/Stop/Reset switch inputs  
Up/Down Presettable Timer and Counter with Alarm  
(up to 99hrs:59min:59sec)
- \* On-Board Alarms:  
Alarm Buzzer, internal or external Horns  
Alarm Relays ( Form C, 10Amp/240V )
- \* NON-GLARE lens
- \* NON-MULTIPLEXING - Camera friendly

Surface Mount ( or optional Flush Mount )  
Water-Proof Enclosure  
Stainless Steel painted with backed enamel



Multifunction  
Remote Control  
Included



**SPECIFICATIONS:**

Supply Voltage:	115V, 208-240V, 50/60Hz 24 or 12V AC/DC
Power:	6VA average
Operating Temperature:	0C to +50C (32F to 122F)
Humidity:	95% RH max. non cond.
Dimensions (w/o back flange)	15" x 5" x 2.5" (38.1cm x 12.7cm x 6.3cm)
Back Flange:	Add 0.5" (1.27cm) on each side and depth
Visibility:	Easy up to 80Ft. (25m)

**HIGH RELIABILITY** SELENA Clocks are ideal for **DIRECT REPLACEMENT** of obsolete and failing system clocks like round electro-mechanical clocks.

Just take old ones down and hang up SELENA Clocks. No additional mounting brackets or wiring necessary.

All functions and presets may be accessed via hand held remote control just like TV remote. If Power Fails, even **WITHOUT** Battery clock will accurately work for up to 2 weeks. With Auto-dimming option display will dimm down automatically in the evening or when lights are turned off. Display will become brighter with bright ambient light.

Inside and Outside Temperature Display option shows current weather conditions. Alarm buzzer and thermostatic, internal relay can control heating or cooling. Relaxing, No-Flicker, camera friendly display technology (new). Choose Thermometer, Timer, Alarm Clock functions with Remote Control.

**Best priced on the market. Most Features.**  
**Easiest to INSTALL and USE in its class.**

