

DIGITAL TIMER

model: series SDT-2-HP-.....

SPECIFICATIONS:

Supply Voltage: 120Vac or 208-240Vac, 60 or 50 Hz.
12 or 24V AC/DC
Power Cons.: 2.5VA max.
Internal relays: 1 pole, N.O.
Contact rating: 30 Amp, 240 Vac max.,
Load conn.: Common or Independent from Supply

Wiring:
Power: Quick Connect 0.25" male
Load Quick Connect 0.25" male

Display: Red LED, 3 digits, 0.36" high
Error detect: Yes, Automatic
Timer mode: Interval or delayed interval
Timer Preset range: CUSTOM
Preset resol.: CUSTOM
Preset control: Rotary on face plate appx. 250 deg. rotation

OPTIONS:
Remote, wired
Start/Stop: Dry contact

Delay-before-start
Preset range: CUSTOM

Timer ambient operating temperature: 0 to +70C
Timer ambient operating humidity: 85% RH max.
non-condensing
Storage temperature: -20C to +90C

Size: Fits in 1-gang electrical wiring box
Dimensions: 1-3/4" x 2.75" x 2.5" (45mm x 70mm x 64mm) (WxHxD)
Face Plate: Stainless Steel 2.75" x 4.5" (70mm x 114mm)
with plastic decal (may be customized)

