



WIRING FOR 2 HIGH POWER LOADS AND 2 ADDITIONAL RELAYS FOR LIGHT, PUMP, FAN ETC... ALL SUPPLY FOR LOADS AND CONTROLLER SEPARATED

DW9




WIRING FOR MOTOR AND LIGHT OR OVERHEAT (or Freeze) PUMP ON THE SAME POWER LINE WITHOUT ADDITIONAL RELAY

DW12




AND THE SAME SUPPLY FOR CONTROLLER

DW10



WIRING FOR COOLING MOTOR (FAN) AND HEATER ON THE SAME POWER LINE WITHOUT ADDITIONAL RELAY

DW11



WIRING FOR 2 HIGH POWER MOTORS AND ADDITIONAL RELAY FOR OVERHEAT OR FREEZE PROTECTION AND WITH SEPARATE SUPPLY FOR CONTROLLER DW13

MOTOR, FAN or PUMP IT IS ADVISEABLE THAT A SNUBBER BE INSTALLED ACROSS THE COIL
OF AN INDUCTIVE LOAD
TO MINIMIZE THE GENERATED
INTERFERENCE 100 ohm 0.047uF (approximate values as shown) Model DSD2-...1HP or 2HP or DSD3-...1HP or 2HP 2 TEMPERATURE SENSOR PROBES

FOR THERMOSTATS WITH 2CH (COOL/HEAT) OPTION

WIRING FOR COOLING MOTOR (FAN) ON THE SAME POWER LINE WITHOUT ADDITIONAL RELAY

DW14